



AUSTRALIAN RAIL TRACK CORPORATION LTD

This document has been adopted by the ARTC with the permission of the NSW Government and will continue to apply under the authority of the ARTC General Manager Infrastructure, Strategy & Performance until further notice

Discipline

Engineering Standard - NSW

Category

Electrical

Title

Polarity of AC Signalling Supplies

Reference Number

PCS 06 - (RIC Standard: EP 90 30 00 01 SI)

Document Control

Status	Date	Prepared	Reviewed	Endorsed	Approved
Issue 1 Revision 1	Mar 05	Standards and Systems	Signalling Standards Engineer	GM Infrastructure Strategy & Performance	Safety Committee
		Refer to Reference Number	T Moore	M Owens	Refer to minutes of meeting 24/01/05

Disclaimer

Australian Rail Track Corporation has used its best endeavors to ensure that the content, layout and text of this document is accurate, complete and suitable for its stated purpose. It makes no warranties, express or implied, that compliance with the contents of this document shall be sufficient to ensure safe systems of work or operation. Australian Rail Track Corporation will not be liable to pay compensation in respect of the content or subsequent use of this document for any other purpose than its stated purpose or for any purpose other than that for which it was prepared except where it can be shown to have acted in bad faith or there has been willful default.

Document Approval

The technical content of this document has been approved by the relevant ARTC engineering authority and has also been endorsed by the ARTC Safety Committee.

Document Supply and Control

The Primary Version of this document is the electronic version that is available and accessible on the Australian Rail Track Corporation Internet and Intranet website.

It is the document user's sole responsibility to ensure that copies are checked for currency against the Primary Version prior to its use.

Copyright

The information in this document is Copyright protected. Apart from the reproduction without alteration of this document for personal use, non-profit purposes or for any fair dealing as permitted under the Copyright Act 1968, no part of this document may be reproduced, altered, stored or transmitted by any person without the prior written consent of ARTC.

About This Standard

The safe operation of 50Hz a.c. signalling track circuits relies on alternate polarities (phase) of adjacent section track feeds. This document sets out the procedures to be followed to ensure the correct phasing of normal supplies to adjacent signalling locations. It also deals with ensuring that the normal and backup supplies at each location are in phase.

Document History

Primary Source – RIC Standard EP 09 30 00 01 SI Version 2.0

List of Amendments –

ISSUE	DATE	CLAUSE	DESCRIPTION
1.1	11/03/2005	Disclaimer	Minor editorial change

Contents

1 Introduction	6
2 Procedure	6
2.1 Locations with no Backup Supply	6
2.2 Locations with Backup Supply	6

1 Introduction

The safe operation of 50Hz a.c. signalling track circuits relies on alternate polarities of adjacent section track feeds. Therefore correct phasing of power supply transformers (to within 60 must be maintained so that track circuits at the extremity of one supply transformer maintain the correct polarity with respect to the track circuit at the extremity of the adjacent supply transformer. This requirement does not exist for audio frequency jointless track circuits.

2 Procedure

2.1 Locations with no Backup Supply

- a) When the connections of 2kV transformers at locations with submains are being changed, they are to be phased out against the submain at the completion of the work.
- b) If it was not possible to check the phasing before the work commenced when a normal supply was worked on (eg a transformer failure of a normal supply) the Signal Engineer must be informed so that the a.c. track circuits at the extremities of the area fed from the location can be checked for correct phasing with the track circuits fed from an adjacent power supply.
- c) If in any doubt about the correct phasing of the signalling supplies contact the relevant Signalling Engineer.

2.2 Locations with Backup Supply

- a) When the polarity of a normal supply is likely to be altered by work, the phasing is to be checked against the emergency supply before work commences and checked again when work is complete.
- b) If it was not possible to check the phasing before the work commenced when a normal supply was worked on (eg a transformer failure of a normal supply) it is to be phase checked against the emergency and the Signalling Engineer informed so that the a.c. track circuits at the extremities of the area fed from the location can be checked for correct phasing with the track circuits fed from an adjacent power supply. (It is possible that the phase of a Local electricity Distributor backup supply could have been changed at some previous time. Distributors will not guarantee phases will not change, only that phase rotation will not change).
- c) If in any doubt about the correct phasing of the signalling supplies contact the Signalling Engineer.
- d) When an emergency supply is being commissioned or worked on, it is to be phased out against the normal supply at the completion of the work.