

Curve Register - Benalla to Oaklands



From Km	To Km	Track	Curve Direction	Minimum Radius	Maximum Radius	Cant	Up Transition Length	Down Transition Length	Curve Speed	Line Speed	Cant Deficiency
(km)	(km)			(m)	(m)	(mm)	(m)	(m)	(kph)	(kph)	(mm)
196.5	196.75	Single	R/Hand	744	764	70	60	55	70		28.0
198.2	198.79	Single	L/Hand	785	825	70	55	55	70		28.0
203.6	204.11	Single	R/Hand	1529	1811	40	60	45	70		3.3
206.39	207.71	Single	L/Hand	1710	1811	40	60	70	70		0.0
209.12	209.6	Single	R/Hand	1106	1106	50	60	40	70		-2.1
211.4	211.49	Single	R/Hand	2072	2072	30	20	20	70		6.7
211.52	211.6	Single	L/Hand	2072	2072	30	20	20	70		4.4
212.01	212.08	Single	L/Hand	825	825	50	30	30	70		18.9
217.22	218.41	Single	R/Hand	1931	2233	30	45	40	70		-7.1
228.33	228.44	Single	L/Hand	1609	1609	40	40	30	70		-7.1
228.44	228.56	Single	R/Hand	1700	1700	40	30	55	70		-7.1
230.36	230.71	Single	R/Hand	2414	3219	20	40	20	70		-7.1
231.96	232.32	Single	L/Hand	2635	2897	20	45	40	70		-1.7
233.71	234.12	Single	L/Hand	724	785	70	60	45	70		-7.1
237.06	237.41	Single	R/Hand	785	925	70	60	65	70		-7.1
237.96	238.04	Single	L/Hand	2816	2816	30	20	20	70		-4.5
238.04	238.11	Single	R/Hand	2816	2816	30	20	20	70		3.3
239.09	239.16	Single	R/Hand	2816	2816	30	20	20	70		5.6
239.16	239.22	Single	L/Hand	2816	2816	30	20	20	70		5.6
240.14	240.67	Single	R/Hand	604	966	80	20	50	60		26.8
241.3	241.43	Single	L/Hand	2816	2816	30	20	20	70		26.8
241.43	241.54	Single	R/Hand	2816	2816	30	20	20	70		52.3
243.11	243.42	Single	R/Hand	4144	4144	20	20	20	70		22.3
243.45	243.57	Single	L/Hand	1208	1208	50	40	45	70		31.4
252.27	252.74	Single	L/Hand	1811	1811	30	45	45	70		-5.6
255.66	256.42	Single	R/Hand	1811	1811	30	30	30	70		-19.6
258.76	259.06	Single	L/Hand	603	603	80	50	75	70		21.7
259.13	259.49	Single	L/Hand	603	603	80	90	60	70		-5.5
260.17	260.3	Single	R/Hand	402	402		30		40		-22.8
260.3	260.44	Single	R/Hand	402	402	30		30	40		-22.8
260.56	260.8	Single	L/Hand	230	290	60	40	40	40		-22.8
261.14	261.4	Single	R/Hand	604	604	60	40	40	50		-22.8
261.81	262	Single	L/Hand	1609	1609	40	30	30	50		-29.2
263.23	263.56	Single	R/Hand	402	402	60	40	40	50		-27.3
264.29	264.68	Single	L/Hand	603	603	60	40	40	50		-27.3
271.24	271.43	Single	R/Hand	1207	1207	50	30	30	50		-22.8

Curve Register - Benalla to Oaklands



From Km	To Km	Track	Curve Direction	Minimum Radius	Maximum Radius	Cant	Up Transition Length	Down Transition Length	Curve Speed	Line Speed	Cant Deficiency
(km)	(km)			(m)	(m)	(mm)	(m)	(m)	(kph)	(kph)	(mm)
272.28	272.44	Single	L/Hand	1207	1207	50	30	30	50		-19.6
274.18	274.29	Single	R/Hand	1207	1207	50	30	30	50		-29.2
274.81	274.94	Single	L/Hand	1207	1207	50	30	30	50		-22.8
281.36	282	Single	R/Hand	805	805	70	45	45	50		-19.6
282.6	283	Single	R/Hand	1006	1006	60	40	40	50		-22.8
284.15	284.76	Single	R/Hand	1006	1006	60	40	40	50		-27.3
287.25	287.54	Single	L/Hand	1207	1207	50	30	30	50		-27.3
288.65	288.81	Single	R/Hand	1609	1609	40	30	30	50		2.7
289.97	291.04	Single	L/Hand	805	805	70	45	30	50		-22.8
292.84	293.01	Single	L/Hand	1207	1207	50	30	30	50		-27.3
296.67	297.05	Single	R/Hand	1609	1609	40	30	30	50		-22.8
298.63	298.95	Single	L/Hand	1207	1207	50	30	30	50		-22.8
301.3	301.71	Single	R/Hand	1006	1006	60	40	40	50		-22.8
302.5	302.89	Single	L/Hand	1006	1006	60	40	40	50		-25.5
303.48	303.73	Single	L/Hand	1006	1006	30	30	30	50		-25.5
303.97	304.3	Single	R/Hand	1207	1207	50	30	30	50		58.8
307.62	307.98	Single	L/Hand	1006	1006	60	40	40	50		0.0
312.35	312.64	Single	L/Hand	1207	1207	50	30	30	50		0.0
313.79	313.88	Single	R/Hand	1207	1207	50	30	30	50		0.0
314.55	315.15	Single	R/Hand	1207	1207	50	30	30	50		0.0
316.7	317.25	Single	R/Hand	603	603	80	50	50	50		0.0
317.94	318.74	Single	R/Hand	603	603	80	50	50	50		0.0
320.99	321.11	Single	R/Hand	302	302	50	30	30	50		0.0