

Curve Register - Maroona to Portland



From Km	To Km	Track	Curve Direction	Minimum Radius	Maximum Radius	Cant	Up Transition Length	Down Transition Length	Curve Speed	Line Speed	Cant Deficiency
(km)	(km)			(m)	(m)	(mm)	(m)	(m)	(kph)	(kph)	(mm)
232.77	233.26	Single	R/Hand	1448	1649	50	60	40	80		2.0
237.19	237.66	Single	R/Hand	784	825	80	55	50	80		16.0
239.84	240.18	Single	L/Hand	1810	2072	40	45	45	80		1.0
241.73	242.51	Single	L/Hand	1267	1448	70	60	45	80		-11.0
245.49	245.94	Single	R/Hand	3420	3882	20	40	30	80		2.0
246.23	246.7	Single	R/Hand	1971	1971	40	40	40	80		-2.0
247.06	247.69	Single	L/Hand	2612	2612	40	25	25	80		-12.0
251.13	251.84	Single	R/Hand	805	805	80	50	50	80		13.0
256.72	257.07	Single	L/Hand	4000	4000	20	0	0	80		-2.0
263.14	263.51	Single	L/Hand	1710	2897	40	25	45	80		4.0
268.18	268.92	Single	R/Hand	1267	1267	70	45	45	80		-11.0
273.52	274.26	Single	L/Hand	1448	1710	50	40	40	80		2.0
276.52	277.16	Single	R/Hand	1609	1609	50	30	30	80		-3.0
280.46	280.61	Single	L/Hand	4023	4023	20	0	0	80		-2.0
283.82	284.15	Single	R/Hand	1207	1207	70	45	45	80		-8.0
285.16	286.05	Single	L/Hand	3219	3219	30	30	30	80		-7.0
286.07	286.86	Single	R/Hand	3219	3219	30	30	30	80		-7.0
287.9	288.51	Single	L/Hand	1600	1600	50	45	45	80		-3.0
290.48	291.37	Single	L/Hand	4000	4000	20	0	0	80		-2.0
292.1	293	Single	R/Hand	2000	2000	40	25	25	80		-3.0
295.58	295.97	Single	R/Hand	1200	1200	70	45	45	80		-7.0
296.38	298.01	Single	L/Hand	1600	2400	50	30	30	80		-3.0
302.6	303.12	Single	R/Hand	1600	1600	50	30	30	80		-3.0
306.06	306.13	Up	R/Hand			0			80		0.0
306.99	307.06	Up	R/Hand			0			80		0.0
307.09	307.16	Up	L/Hand			0			80		0.0
309.84	310.2	Single	L/Hand	1609	1609	50	30	30	80		-3.0
311.24	311.31	Single	L/Hand			0			80		0.0
311.31	311.38	Single	R/Hand			0			80		0.0
311.66	311.74	Single	R/Hand			0			80		0.0
311.74	311.81	Single	L/Hand			0			80		0.0
315.39	316.07	Single	L/Hand	1408	1408	50	40	40	80		3.0
316.91	317.04	Single	L/Hand						80		0.0
317.1	317.26	Single	L/Hand						80		0.0

Curve Register - Maroona to Portland



From Km	To Km	Track	Curve Direction	Minimum Radius	Maximum Radius	Cant	Up Transition Length	Down Transition Length	Curve Speed	Line Speed	Cant Deficiency
(km)	(km)			(m)	(m)	(mm)	(m)	(m)	(kph)	(kph)	(mm)
317.29	317.59	Single	L/Hand						80		0.0
318.27	318.33	Single	L/Hand			30	20	20	80		0.0
318.33	318.41	Single	R/Hand			30	20	20	80		0.0
318.43	319.4	Single	R/Hand	1207	1207	70	70	70	80		-8.0
328.8	329.87	Single	R/Hand	4023	4023	20	45	45	80		-2.0
337.2	337.26	Up	R/Hand						80		0.0
338.17	338.25	Up	R/Hand						80		0.0
338.28	338.35	Single	L/Hand						80		0.0
338.99	339.88	Single	L/Hand	1187	1247	70	50	50	80		-7.0
341.28	341.78	Single	L/Hand	1609	1609	50	30	30	80		-3.0
343.15	344.11	Single	R/Hand	1609	1609	50	30	30	80		-3.0
349.53	350.34	Single	L/Hand	724	724	80	55	55	80		24.0
350.49	350.88	Single	L/Hand	1710	1710	40	25	25	80		4.0
354.4	355.06	Single	R/Hand	805	1167	70	45	45	80		23.0
365.07	365.5	Single	L/Hand	1207	1207	70	45	45	80		-8.0
365.88	366.77	Single	R/Hand	1005	1207	70	75	75	80		5.0
367.34	368.19	Single	L/Hand	1148	1710	50	40	40	80		15.0
368.42	368.9	Single	R/Hand	1408	1609	50	40	40	80		3.0
369.16	369.59	Single	R/Hand	785	825	80	55	55	80		16.0
369.59	370.29	Single	L/Hand	764	945	80	50	50	80		19.0
370.41	371.38	Single	R/Hand	1127	1247	70	45	45	80		-3.0
371.51	371.94	Single	L/Hand	1127	1710	50	40	40	80		17.0
373.63	374.12	Single	R/Hand	1066	1368	70	45	45	80		0.0
374.12	374.85	Single	L/Hand	1106	1207	70	55	55	80		-2.0
376.82	377.26	Single	R/Hand	1448	1710	50	60	60	80		2.0
378.64	378.81	Single	L/Hand						80		0.0
378.82	378.93	Single	L/Hand						80		0.0
378.94	379.2	Single	L/Hand						80		0.0
379.57	379.65	Single	R/Hand						80		0.0
379.68	380.3	Single	L/Hand	2012	2012	40	25	25	80		-3.0
382.15	382.61	Single	R/Hand	2012	2012	40	60	60	80		-3.0
390.39	390.82	Single	R/Hand	1609	1609	50	45	45	80		-3.0
390.9	391.05	Single	R/Hand	805	825	80	50	50	80		13.0
391.28	391.53	Single	L/Hand	825	905	80	50	50	80		11.0

Curve Register - Maroona to Portland



From Km	To Km	Track	Curve Direction	Minimum Radius	Maximum Radius	Cant	Up Transition Length	Down Transition Length	Curve Speed	Line Speed	Cant Deficiency
(km)	(km)			(m)	(m)	(mm)	(m)	(m)	(kph)	(kph)	(mm)
391.55	391.99	Single	R/Hand	563	624	80	55	55	80		54.0
392.03	392.23	Single	R/Hand	563	624	80	50	50	80		54.0
392.23	392.92	Single	L/Hand	583	624	80	50	50	80		49.0
392.92	393.17	Single	R/Hand	724	825	80	50	50	80		24.0
393.56	394.48	Single	R/Hand	764	825	80	60	60	80		19.0
394.53	394.83	Single	L/Hand	543	624	80	60	60	80		59.0
395.54	396.24	Single	L/Hand	583	604	80	50	50	80		49.0
396.24	396.72	Single	R/Hand	724	825	80	50	50	80		24.0
397.18	397.39	Single	L/Hand	724	724	80	60	60	80		24.0
398	398.41	Single	R/Hand	764	825	80	50	50	80		19.0
399.45	399.75	Single	L/Hand	583	604	80	50	50	80		49.0
400.52	401.26	Single	R/Hand	744	825	80	70	70	80		21.0