



**AUSTRALIAN RAIL TRACK CORPORATION LTD**

*This document has been adopted by the ARTC with the permission of the NSW Government and will continue to apply under the authority of the ARTC General Manager Infrastructure, Strategy & Performance until further notice*

**Discipline**  
**Engineering Standard – NSW**

**Category**  
**Signalling**

**Title**  
**Single Line Sections**

**Reference Number**  
**SDS 07 – (RIC Standard: SC 00 13 01 07 SP)**

**Document Control**

<b>Status</b>	<b>Date</b>	<b>Prepared</b>	<b>Reviewed</b>	<b>Endorsed</b>	<b>Approved</b>
Issue 1 Revision 2	Mar 05	Standards and Systems	Standards Engineer	GM Infrastructure Strategy & Performance	Safety Committee
		Refer to Reference Number	H Olsen	M Owens	Refer to minutes of meeting 12/08/04

## **DISCLAIMER**

Australian Rail Track Corporation has used its best endeavors to ensure that the content, layout and text of this document is accurate, complete and suitable for its stated purpose. It makes no warranties, express or implied, that compliance with the contents of this document shall be sufficient to ensure safe systems of work or operation. Australian Rail Track Corporation will not be liable to pay compensation in respect of the content or subsequent use of this document for any other purpose than its stated purpose or for any purpose other than that for which it was prepared except where it can be shown to have acted in bad faith or there has been willful default.

## **DOCUMENT APPROVAL**

The technical content of this document has been approved by the relevant ARTC engineering authority and has also been endorsed by the ARTC Safety Committee.

## **DOCUMENT SUPPLY and CONTROL**

The Primary Version of this document is the electronic version that is available and accessible on the Australian Rail Track Corporation Internet and Intranet website.

It is the document user's sole responsibility to ensure that copies are checked for currency against the Primary Version prior to its use.

## **COPYRIGHT**

The information in this document is Copyright protected. Apart from the reproduction without alteration of this document for personal use, non-profit purposes or for any fair dealing as permitted under the Copyright Act 1968, no part of this document may be reproduced, altered, stored or transmitted by any person without the prior written consent of ARTC.

## About This Standard

This Principle addresses the requirements for the provision of block circuit controls on single line sections.

# Document History

**Primary Source** – RIC Standard SC 00 13 01 07 SP Version 3.0

## List of Amendments –

<b>ISSUE</b>	<b>DATE</b>	<b>CLAUSE</b>	<b>DESCRIPTION</b>
1.1	01/09/2004		▪ Reformatting to ARTC Standard
1.2	14/03/2005	Disclaimer	▪ Minor editorial change ▪ Footer reformatted

# Contents

<b>7 Single Line Sections .....</b>	<b>6</b>
<b>7.1 Principle No. 7.1 - Single Line Section Control In Single Line Areas .....</b>	<b>6</b>
7.1.1 Introduction .....	6
7.1.2 Requirements .....	6
7.1.3 Half-Pilot Staff .....	6
7.1.4 Pilot Staff Lock Designation Plate .....	7

## 7 Single Line Sections

### 7.1 Principle No. 7.1 - Single Line Section Control In Single Line Areas.

#### 7.1.1 Introduction

This Principle addresses the requirements for the provision of block circuit controls on single line sections.

#### 7.1.2 Requirements

The following requirements shall be met before a signal controlling the entrance to a single line block section is permitted to clear and continuously thereafter.

- The directly opposing signal(s) controlling the entrance to the single line block section at the opposite end, shall be proved normal.
- Intermediate directly opposing signals within the single line block section controlling movements in the opposite direction, shall be proved normal.
- The track circuits between the overlap clearance point of the signal to be cleared and the directly opposing signal(s) controlling the entrance to the single line block section at the opposite end, shall be clear unless occupied by a train being signalled through diverging points which prevent it from proceeding onto the overlap track or unless occupied by a preceding train travelling in the same direction.
- The half-pilot staffs at each end of the single line block section shall be proved normal.
- Any releasing switches situated in the single line section shall be proved normal.
- Any trapping protection on points operated from ground frames situated in the single line section shall be proved normal.
- Other points detection shall be proved normal as applicable.
- Directional controls associated with operation of level crossing equipment within the single line section shall be proved normal.
- The block control circuit closed for a period of fifteen seconds immediately before the signal controlling the entrance to the single line block section clears to show a proceed aspect.

This is not required where the track circuit equipment provided has intrinsic delayed pick characteristics.

#### 7.1.3 Half-Pilot Staff

On single line track control or track block sections, or on bidirectional signalling sections on double lines, pilot staff working under section signalling failure conditions may be facilitated by the installation at each end of the section of a half pilot staff held captive in a pilot staff lock erected on

or near the signal(s) controlling entry to the single line section. The half pilot staffs from each end are joined together to form the one pilot staff for the section.

The following two examples show the type of details required to be inscribed on half pilot staffs in single line areas.

TARANA TA32  (to WALLERAWANG)	WALLERAWANG WG15  (to TARANA)	Interlocking and Signal where Half Pilot Staff located.  Interlocking at opposite end of single line section.
KILBRIDE 05/11  (to WALLAROBBA)	WALLAROBBA 06/12  (to KILBRIDE)	

The signal number is the main line Home/Starting or Starting signal for the single line section concerned and, also applies to the loop, siding, branch line, etc, Home/Starting or Starting signal(s) leading onto the single line section.

#### 7.1.4 Pilot Staff Lock Designation Plate

Designation plates attached to Pilot Staff Locks are to be inscribed with details similar to the following two examples.

<u>HALF PILOT STAFF</u>  WALLERAWANG WG15  to  TARANA TA32	Interlocking and Home/Starting or Starting Signal(s) leading into the single line section.  Interlocking at opposite end of section and opposing Home/Starting or Starting Signal(s) leading into the single line Section.
<u>HALF PILOT STAFF</u>  KILBRIDE 05/11M.11L  to  WALLAROBBA 06/12M.12L	