



AUSTRALIAN RAIL TRACK CORPORATION LTD

This document has been adopted by the ARTC with the permission of the NSW Government and will continue to apply under the authority of the ARTC General Manager Infrastructure, Strategy & Performance until further notice

Discipline
Engineering Standard – NSW

Category
Signalling

Title
Lightning/ Surge Protection - Power Inductors

Reference Number
SPS 37 - (RIC Standard: SC 09 15 04 00 SP)

Document Control

Status	Date	Prepared	Reviewed	Endorsed	Approved
Issue 1 Revision 3	May 05	Standards and Systems	Standards Engineer	GM Infrastructure Strategy & Performance	Safety Committee
		Refer to Reference Number	H Olsen	M Owens	Refer to minutes of meeting 12/08/04

Disclaimer

Australian Rail Track Corporation has used its best endeavors to ensure that the content, layout and text of this document is accurate, complete and suitable for its stated purpose. It makes no warranties, express or implied, that compliance with the contents of this document shall be sufficient to ensure safe systems of work or operation. Australian Rail Track Corporation will not be liable to pay compensation in respect of the content or subsequent use of this document for any other purpose than its stated purpose or for any purpose other than that for which it was prepared except where it can be shown to have acted in bad faith or there has been willful default.

Document Approval

The technical content of this document has been approved by the relevant ARTC engineering authority and has also been endorsed by the ARTC Safety Committee.

Document Supply and Control

The Primary Version of this document is the electronic version that is available and accessible on the Australian Rail Track Corporation Internet and Intranet website.

It is the document user's sole responsibility to ensure that copies are checked for currency against the Primary Version prior to its use.

Copyright

The information in this document is Copyright protected. Apart from the reproduction without alteration of this document for personal use, non-profit purposes or for any fair dealing as permitted under the Copyright Act 1968, no part of this document may be reproduced, altered, stored or transmitted by any person without the prior written consent of ARTC.

About This Standard

This Specification describes the design requirements for Power Inductors with ratings 15A to 200 Amperes to be manufactured and supplied to Australian Rail Track Corporation or contractors to Australian Rail Track Corporation

Document History

Primary Source – RIC Standard SC 09 15 04 00 SP Version 2.0

List of Amendments –

ISSUE	DATE	CLAUSE	DESCRIPTION
1.1	01/09/2004		Reformatting to ARTC Standard
1.2	14/03/2005	Disclaimer	Minor editorial change
1.3	06/05/2005	All	Document reformatted

Contents

1.	Introduction.....	6
2.	Applicable Documents.....	6
3.	Operation Conditions.....	6
4.	Design Requirements.....	6
4.1	Electrical Specifications	6
4.2	Design Considerations.....	7
4.3	Impregnation	7
4.4	Insulation Resistance.....	7
4.5	Terminals	7
4.6	Dimensions	7
4.7	Labelling.....	7

1. Introduction

This Specification describes the design requirements for Power Inductors with ratings 15A to 200 Amperes to be manufactured and supplied to Australian Rail Track Corporation or contractors to Australian Rail Track Corporation.

The Inductor shall form part of the following equipment, which shall provide lightning/surge suppression on AC and DC power supply mains.

- 1) Inductor/Diverter Panel (IDP)
- 2) Inductor/Varistor Panel (IVP)
- 3) Inductor/Varistor/Arrestor Panel (IVAP)

The Inductor shall be referred to as PI-15A, PI-50A, PI-100A or 200A depending on the current rating of the indicator

2. Applicable Documents

- Specification SCP 04 - (Lightning/Surge Protection Requirements)
- Specification SPS 39 - (Lightning/Surge Protection - Inductor/ Diverter Panel (IDP))
- Specification SPS 33 - (Lightning/Surge Protection - Inductor/ Varistor Panel (IVP))
- Specification SC 09 15 05 00 SP - (Lightning/Surge Protection - Inductor/ Varistor/Arrestor Panel (IVAP))

3. Operation Conditions

The inductor shall be capable of operating satisfactorily under the following conditions:

- 1) Ambient Temperature range: - 10C to +70C.
- 2) Humidity: Relative Humidity 0 to 95%

4. Design Requirements

4.1 Electrical Specifications

The inductor is an air-cored inductor with the following ratings.

Power Inductor	Operating Voltage	L	R	Max Continuous Current
PI-15A/240V	120, 240V	25 Micro-H	10 m ohm	25A
PI - 50	120V	25 Micro-H	7 m ohm	80A
PI - 100	120V	25 Micro-H	2 m ohm	160A
PI - 200	120V	25 Micro-H	1.12 m ohm	300A

Inductors designed for higher current ratings than shown above, the values of L & R shall be selected such that the heat rise at full load for an ambient temperature of 70 C shall not exceed 40 C and Voltage drop across the inductor shall not exceed 2.0 Volts at maximum continuous current rating.

4.2 Design Considerations

The cross section area of the conductor shall be based on the continuous current of 80 Amperes for PI-50, 160 Amperes in the case of PI-100 and 25 Amperes in case of PI-15A.

The spacing of the windings and the insulation of the conductor shall be such that the voltage produced by a surge current of 20KA, 8/20 microseconds shall not breakdown the insulation.

The spacing of the windings and the insulation of the conductor shall be such that the coil should be able to withstand a voltage of 30KV generated internally (current flow x impedance of the coil). The beginning and end of the coil should be at the two ends of the coil former or at least separated by 60 millimetres if ended at one end of the former.

The progressive voltage between the turns and the layers of windings (if more than one layer of winding is required) should be carefully considered to provide proper separation and insulating material to withstand the breakdown voltage.

4.3 Impregnation

The coil should be either:

- Vacuum Impregnated, or
- Encapsulated in Epoxy casting, Polyester casting or in Poly Carbonate casting.

4.4 Insulation Resistance

The insulation resistance shall be greater than 100 M-Ohms when measured using an Insulation tester with an injected voltage of 500 V. The test shall be conducted for 1 minute with the body of the inductor immersed in water. The water shall be in a metal tank and the insulation tester applied from either inductor terminal to the water tank.

4.5 Terminals

Terminals shall be M6 and 30 mm long Nickel plated Brass studs provided with 2 washers, a nut and a lock nut for each stud. Appropriate terminals shall be selected for higher current ratings.

4.6 Dimensions

The maximum height of the inductor rated up to 100A shall not exceed 200mm from the mounting surface.

4.7 Labelling

- All labelling shall be permanently affixed, clearly legible, and of a material which shall not fade or deteriorate due to handling, environmental conditions or ageing.

-
- The unit must be fitted with a readily visible label stating PI-15A, PI-50, PI-100 or PI-200A, the manufacturer's identification and the date of manufacture.