



AUSTRALIAN RAIL TRACK CORPORATION LTD

*This document has been adopted by the ARTC with the permission of the NSW Government and will continue to apply under the authority of the ARTC General Manager Infrastructure, Strategy & Performance until further notice*

**Discipline**  
**Engineering Standard – NSW**

**Category**  
**Signalling**

**Title**  
**Lightning/Surge Protection Inductor/Diverter Panel**

**Reference Number**  
**SPS 39 - (RIC Standard: SC 09 15 07 00 SP)**

**Document Control**

<b>Status</b>	<b>Date</b>	<b>Prepared</b>	<b>Reviewed</b>	<b>Endorsed</b>	<b>Approved</b>
Issue 1 Revision 3	May 05	Standards and Systems	Standards Engineer	GM Infrastructure Strategy & Performance	Safety Committee
		Refer to Reference Number	H Olsen	M Owens	Refer to minutes of meeting 12/08/04

## **Disclaimer**

Australian Rail Track Corporation has used its best endeavors to ensure that the content, layout and text of this document is accurate, complete and suitable for its stated purpose. It makes no warranties, express or implied, that compliance with the contents of this document shall be sufficient to ensure safe systems of work or operation. Australian Rail Track Corporation will not be liable to pay compensation in respect of the content or subsequent use of this document for any other purpose than its stated purpose or for any purpose other than that for which it was prepared except where it can be shown to have acted in bad faith or there has been willful default.

## **Document Approval**

The technical content of this document has been approved by the relevant ARTC engineering authority and has also been endorsed by the ARTC Safety Committee.

## **Document Supply and Control**

The Primary Version of this document is the electronic version that is available and accessible on the Australian Rail Track Corporation Internet and Intranet website.

It is the document user's sole responsibility to ensure that copies are checked for currency against the Primary Version prior to its use.

## **Copyright**

The information in this document is Copyright protected. Apart from the reproduction without alteration of this document for personal use, non-profit purposes or for any fair dealing as permitted under the Copyright Act 1968, no part of this document may be reproduced, altered, stored or transmitted by any person without the prior written consent of ARTC.

## **About This Standard**

This Specification describes the general requirements for Inductor/Diverter Panels to be manufactured and supplied to Australian Rail Track Corporation or contractors to Australian Rail Track Corporation.

## Document History

**Primary Source** – RIC Standard SC 09 15 07 00 SP Version 2.0

### List of Amendments –

<b>ISSUE</b>	<b>DATE</b>	<b>CLAUSE</b>	<b>DESCRIPTION</b>
1.1	01/09/2004		Reformatting to ARTC Standard
1.2	14/03/2005	Disclaimer	Minor editorial change
1.3	05/06/2005	All	Document reformatted

## Contents

1.	Introduction.....	6
2.	Applicable Documents.....	6
2.1	Australian Standards.....	6
2.2	ARTC Specifications .....	6
3.	General.....	6
4.	Operation Conditions.....	6
5.	Design Requirements.....	6
5.1	Construction .....	6
5.2	Components.....	6
5.3	Wiring .....	7
5.4	Terminals .....	7
5.5	Labelling.....	7

## 1. Introduction

This Specification describes the general requirements for Inductor/Diverter Panels to be manufactured and supplied to Australian Rail Track Corporation or contractors to Australian Rail Track Corporation.

## 2. Applicable Documents

### 2.1 Australian Standards

AS3000/1991 : Electrical Installations-Building, Structures and Premises.

### 2.2 ARTC Specifications

This Specification refers to the following Specifications:

Specification SPS 37: Lightning/Surge Protection - Power Inductor.

Specification SCP 04: Lightning/Surge Protection Requirements.

## 3. General

Inductor/Diverter Panel shall be required to provide lightning/surge suppression on AC and DC power supply mains.

The panel shall be referred to as IDP-50 or IDP-100 as appropriate. The current ratings shall be 50A and 100A AC or DC for IDP-50 and IDP-100 respectively.

## 4. Operation Conditions

The equipment shall be capable of operating satisfactorily under the following conditions:

- Ambient temperature range -10 to 70 C.
- Relative humidity 0 to 95%.

## 5. Design Requirements

### 5.1 Construction

Construction shall be in accordance with the SRA drawing No D9924. Critical values are the overall size, mounting centres, and the relative position of the input, output and earth terminations.

All components shall be securely mounted on a 10 millimetre panel. The panel shall be made of either paper-based Phenolic or ABS.

All components shall be readily and individually replaceable in case of failure. All material fittings, bolts, nuts, etc shall be Nickel-plated Brass.

### 5.2 Components

The Inductors shall be as specified in Specification 868 for IDP-50 and IDP-100. The Diverter shall be "Bowthorpe" MA2F2.

---

### 5.3 Wiring

All conductors shall be multi-stranded, with sizes and current ratings in accordance with AS3000-1991

Minimum insulation shall be 0.6KV, V75 grade PVC.

All conductors shall be as short and as direct as possible with smooth curves of maximum practical radius.

All conductors shall be terminated with suitable crimp lugs either pre-insulated double-grip type for smaller conductors, or in the case of larger conductors, non-insulated lugs with a heatshrink sleeve applied after crimping. The heat shrink sleeve shall cover the body of the crimp lug and extend at least 15mm over the conductor insulation.

### 5.4 Terminals

The Earth Terminal shall be M6 and 40 millimetre long Nickel plated Brass studs provided with 3 washers, two nuts and one lock nut for each stud.

### 5.5 Labelling

All labelling shall be permanently affixed, clearly legible, and of a material which will not fade due to weathering over time or repeated handling.

Input and Output terminals shall be labelled "Line 1", "Line 2", "Equipment 1" and "Equipment 2" respectively. The Earth terminal shall be labelled "Signalling Earth".

In addition the unit must be fitted with a readily visible label stating "IDP-50" or "IDP-100" as appropriate, the manufacturer's identification and date of manufacture.