



AUSTRALIAN RAIL TRACK CORPORATION LTD

This document has been adopted by the ARTC with the permission of the NSW Government and will continue to apply under the authority of the ARTC General Manager Infrastructure, Strategy & Performance until further notice

Discipline
Engineering Standard – NSW

Category
Signalling

Title
Cables for Railway Signalling Applications - High Frequency Screened Track Circuit Cables.

Reference Number
SPS 48 - (RIC Standard: SC 11 11 13 00 SP)

Document Control

Status	Date	Prepared	Reviewed	Endorsed	Approved
Issue 1 Revision 3	May 05	Standards and Systems	Standards Engineer	GM Infrastructure Strategy & Performance	Safety Committee
		Refer to Reference Number	H Olsen	M Owens	Refer to minutes of meeting 12/08/04

Disclaimer

Australian Rail Track Corporation has used its best endeavors to ensure that the content, layout and text of this document is accurate, complete and suitable for its stated purpose. It makes no warranties, express or implied, that compliance with the contents of this document shall be sufficient to ensure safe systems of work or operation. Australian Rail Track Corporation will not be liable to pay compensation in respect of the content or subsequent use of this document for any other purpose than its stated purpose or for any purpose other than that for which it was prepared except where it can be shown to have acted in bad faith or there has been willful default.

Document Approval

The technical content of this document has been approved by the relevant ARTC engineering authority and has also been endorsed by the ARTC Safety Committee.

Document Supply and Control

The Primary Version of this document is the electronic version that is available and accessible on the Australian Rail Track Corporation Internet and Intranet website.

It is the document user's sole responsibility to ensure that copies are checked for currency against the Primary Version prior to its use.

Copyright

The information in this document is Copyright protected. Apart from the reproduction without alteration of this document for personal use, non-profit purposes or for any fair dealing as permitted under the Copyright Act 1968, no part of this document may be reproduced, altered, stored or transmitted by any person without the prior written consent of ARTC.

About This Standard

This Specification describes the technical requirements for data cables used for railway signalling track circuits operating at audio frequencies. These cables are used extensively in the NSW railway network in audio frequency track circuits. These cables are also being used for Impulse track circuits.

This document details the specification for the manufacture of this cable. Screenings against electro-magnetic and electro-static effects and mechanical protection have been specified.

Document History

Primary Source – RIC Standard SC 11 11 13 00 SP Version 3.0

List of Amendments –

ISSUE	DATE	CLAUSE	DESCRIPTION
1.1	01/09/2004		Reformatting to ARTC Standard
1.2	14/03/2005	Disclaimer	Minor editorial change
1.3	06/05/2005	All	Document reformatted

Contents

1.	Introduction.....	6
2.	Applicable Documents.....	6
2.1	Australian Standards.....	6
2.2	ARTC Specifications	6
3.	Ratings	6
3.1	Voltage	6
3.2	Maximum Continuous Conductor Temperature	6
4.	Construction	6
4.1	Length	6
4.2	Conductor.....	6
4.3	Insulation.....	6
4.4	Twisting	7
4.5	Screen.....	7
4.6	Supplementary Insulation (Sheath).....	7
4.7	Nylon Covering.....	7
5.	Identification	7
5.1	Marking on Cables	7
5.2	Marking on Reels	7
6.	Tests.....	7
7.	Inspection & acceptance testing.....	7

1. Introduction

This Specification describes the general requirements for single pair shielded cables, to be manufactured and supplied to Australian Rail Track Corporation for the use in signalling applications in the NSW rail network.

The cable shall consist of 2 x 7/0.50mm White, Black PVC/Aluminium shield/Black PVC/Nylon (core colours White & Black)

Specification SPS 40 Cables for Railway Signalling Applications - General Requirements shall form part of this Specification.

2. Applicable Documents

2.1 Australian Standards

This Specification refers to the following Australian Standards:

AS 1125: Conductors in Insulated Electric Cables and Flexible Cords

AS 5000-1999 Electric Cables – Polymeric insulated for working voltages up to and including 0.6/1KV

2.2 ARTC Specifications

This Specification refers to the following Australian Rail Track Corporation Specifications:

Specification SPS 40: Cables for Railway Signalling Applications-General Requirements

3. Ratings

3.1 Voltage

Voltage rating shall be 0.6/1KV.

3.2 Maximum Continuous Conductor Temperature

75 C

4. Construction

4.1 Length

Length shall be as specified in Specification SPS 40 Cables For Railway Signalling Applications - General Requirements

4.2 Conductor

The conductor shall be annealed, un-tinned, high conductivity copper consisting of seven (7) strands of 0.5mm wire laid up with a length of lay between 28 and 45mm.

4.3 Insulation

Each conductor shall be individually insulated with V75 P.V.C. to a nominal radial thickness of 0.8mm. One conductor shall be coloured black, the other white.

4.4 Twisting

Conductors shall be laid up with a lay as short as good construction will permit but not exceeding 50mm.

4.5 Screen

The laid up cores are to be covered with a Polyester (Mylar) backed Aluminium tape 0.05mm thick giving 100% coverage at the prescribed minimum bending radius of the cable. A drain wire consisting of seven (7) strands of 0.25mm is to be provided continuously throughout the cable so as to give intimate electrical contact with the Polyester (Mylar) backed aluminium tape

Non-hygroscopic cable filler may be used if required.

4.6 Supplementary Insulation (Sheath)

The supplementary insulation shall be black V75 PVC. The sheath shall have a nominal thickness of 2mm but shall not be less than 1.7mm thick at any point.

4.7 Nylon Covering

A Nylon covering shall be provided, having an average radial thickness as specified in Specification SPS 40 Cables For Railway Signalling Applications - General Requirements. The nylon shall be ultra-violet stabilised type 11 or 12 and coloured black.

5. Identification

5.1 Marking on Cables

Additionally, the size of the conductors shall be marked on the cables.

5.2 Marking on Reels

An additional legend "T.T. Screened Underground" shall be marked on the reels.

6. Tests

In addition, the cores shall be spark tested at 6kV before laying up. The results of the tests shall be recorded in the attached test report.

7. Inspection & acceptance testing

The results of the tests shall be recorded in the test report specified in Specification SPS 40 Cables For Railway Signalling Applications - General Requirements.

Inspection and acceptance test procedure shall be as detailed in Specification SPS 40.