

NEW EQUIPMENT AND SYSTEM APPROVAL CERTIFICATE

Certificate No. S 05-2703-207A

Approval date 12/09/2018
 Approved by GM Technical Standards
 Report no. TAS 05-2703-PB207A
 Report date 24 August 2018

This certificate is issued to

Supplier Powerbox Australia Pty Ltd
 4 Beaumont Road,
 Mt Kuring-Gai NSW 2080 Australia

In respect of

Manufacturer Powerbox Australia Pty Ltd
Product description Powerbox PBIH DC/DC Converters
Item identification Refer to Approved Item List in Table 1.
Application ARTC Network Wide
Relevant Standards SPS 02 Environmental Conditions
 SPS 05 Electrical & Electronic Components (Ratings & Construction Requirements)
 SPS 22 Power Supply Units for Signalling Equipment – General Requirements
 ESD-09-01 Signalling Power Systems
 SPS 28 Power Supply Units for Signalling Equipment – DC Filtered Units

Conditions of Approval

General	[1]. The units are suitable to be installed in equipment housings where temperatures do not exceed 50°C. Derating must be considered between >50°C to a maximum temperature of 60°C at 3.5%/K. Table 1 specifies the conditions of use for each unit.
	[2]. The units are not to be installed in steel or aluminum location cupboards, unless the cupboards are double skinned or a sun shelter is installed.
	[3]. There are no field serviceable components within the units, any failed units shall be replaced. Units shall only be repaired by Powerbox Australia Pty Ltd.
Supplier	[4]. The supplier or manufacturer must advise ARTC of any changes made

NEW EQUIPMENT AND SYSTEM APPROVAL CERTIFICATE

	to the product or system which may alter its identification, performance characteristics, form, fit, function or processes required for correct usage so that this approval can be revised or reviewed.
	[5]. A general condition of approval is that the supplier remains accredited to ISO 9001 specifically for these products and ARTC is advised on a 12 monthly basis that accreditation is current. ARTC reserves the right to conduct its own audit of the manufacture and supply of these components to AS19001:2003.

Note/Comments NIL.

Issue date

12/09/2018

Expiry date N/A

Issued by



John Furness
ARTC Manager Standards

Table 1 - Approved Item List – PBIH DC/DC Converters

The following lists the individual types of Powerbox PBIH DC/DC Converters manufactured by Powerbox Australia Pty Ltd which are type approved for use in signalling installations on ARTC infrastructure under Type Approval Certificate **S05-2703-207A** subject only to any conditions shown on that Certificate and the Conditions of Use shown against individual types.

Part Number	Input DC	Output DC	Output Power	MTBF Data (Hours)	D-Rating Factor
PBIH-1205G	9.2 - 16V DC	5V @ 5A	25W	887069.88	0 - 50°C (Full Power) D-Rating of 0.88W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1205J	9.2 - 16V DC	5V @ 8A	40W	824769.48	0 - 50°C (Full Power) D-Rating of 1.4W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1205M	9.2 - 16V DC	5V @ 18A	90W	460400.92	0 - 50°C (Full Power) D-Rating of 2.97W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1205R	9.2 - 16V DC	5V @ 27A	135W	416004.53	0 - 50°C (Full Power) D-Rating of 4.72W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1212J	9.2 - 16V DC	12V @ 3.3A	40W	826705.91	0 - 50°C (Full Power) D-Rating of 1.4W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1212M	9.2 - 16V DC	12V @ 9A	108W	475646.88	0 - 50°C (Full Power) D-Rating of 3.56W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1212R	9.2 - 16V DC	12V @ 13A	156W	419445.49	0 - 50°C (Full Power) D-Rating of 5.46W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1215J	9.2 - 16V DC	15V @ 2.7A	41W	826432.62	0 - 50°C (Full Power) D-Rating of 1.43W per Degree Celcius above 50°C to a maximum of 60°C.

NEW EQUIPMENT AND SYSTEM APPROVAL CERTIFICATE

Part Number	Input DC	Output DC	Output Power	MTBF Data (Hours)	D-Rating Factor
PBIH-1215M	9.2 - 16V DC	15V @ 7A	105W	482681.39	0 - 50°C (Full Power) D-Rating of 3.46W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1215R	9.2 - 16V DC	15V @ 10A	150W	419720.13	0 - 50°C (Full Power) D-Rating of 5.25W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1224J	9.2 - 16V DC	24V @ 1.7A	41W	826705.91	0 - 50°C (Full Power) D-Rating of 1.43W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1224M	9.2 - 16V DC	24V @ 4.5A	108W	483502.88	0 - 50°C (Full Power) D-Rating of 3.56W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1224R	9.2 - 16V DC	24V @ 6.5A	156W	428485.73	0 - 50°C (Full Power) D-Rating of 5.46W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1248M	9.2 - 16V DC	48V @ 2.2A	106W	483502.88	0 - 50°C (Full Power) D-Rating of 3.49W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-1248R	9.2 - 16V DC	48V @ 3.3A	158W	428485.73	0 - 50°C (Full Power) D-Rating of 5.53W per Degree Celcius above 50°C to a maximum of 60°C.
Part Number	Input DC	Output DC	Output Power	MTBF Data (Hours)	D-Rating Factor
PBIH-2412J	19 - 32V DC	12V @ 4.3A	52W	814358.77	0 - 50°C (Full Power) D-Rating of 1.82W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2412M	19 - 32V DC	12V @ 9A	108W	739207.57	0 - 50°C (Full Power) D-Rating of 3.56W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2412R	19 - 32V DC	12V @ 14A	168W	419603.89	0 - 50°C (Full Power) D-Rating of 5.88W per Degree Celcius above 50°C to a maximum of 60°C.



NEW EQUIPMENT AND SYSTEM APPROVAL CERTIFICATE

Part Number	Input DC	Output DC	Output Power	MTBF Data (Hours)	D-Rating Factor
PBIH-2415J	19 - 32V DC	15V @ 3.4A	51W	814093.59	0 - 50°C (Full Power) D-Rating of 1.78W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2415M	19 - 32V DC	15V @ 7A	105W	740269.16	0 - 50°C (Full Power) D-Rating of 3.46W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2415R	19 - 32V DC	15V @ 11A	165W	427964.94	0 - 50°C (Full Power) D-Rating of 5.77W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2424J	19 - 32V DC	24V @ 2.5A	60W	814358.77	0 - 50°C (Full Power) D-Rating of 2.1W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2424M	19 - 32V DC	24V @ 5A	120W	598114.74	0 - 50°C (Full Power) D-Rating of 3.96W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2424R	19 - 32V DC	24V @ 7A	168W	428485.73	0 - 50°C (Full Power) D-Rating of 5.88W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2448M	19 - 32V DC	48V @ 2A	96W	740269.16	0 - 50°C (Full Power) D-Rating of 3.16W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-2448R	19 - 32V DC	48V @ 3.5A	168W	428485.73	0 - 50°C (Full Power) D-Rating of 5.88W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4812J	38 - 63V DC	12V @ 4.3A	52W	813762.35	0 - 50°C (Full Power) D-Rating of 1.82W per Degree Celcius above 50°C to a maximum of 60°C.

NEW EQUIPMENT AND SYSTEM APPROVAL CERTIFICATE

Part Number	Input DC	Output DC	Output Power	MTBF Data (Hours)	D-Rating Factor
PBIH-4812M	38 - 63V DC	12V @ 9A	108W	716794.5	0 - 50°C (Full Power) D-Rating of 3.56W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4812R	38 - 63V DC	12V @ 14A	168W	425662.33	0 - 50°C (Full Power) D-Rating of 5.88W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4815J	38 - 63V DC	15V @ 3.4A	51W	813497.55	0 - 50°C (Full Power) D-Rating of 1.78W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4815M	38 - 63V DC	15V @ 7A	105W	716589.5	0 - 50°C (Full Power) D-Rating of 3.46W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4815R	38 - 63V DC	15V @ 11A	165W	434296.04	0 - 50°C (Full Power) D-Rating of 5.77W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4824J	38 - 63V DC	24V @ 2.5A	60W	814956.07	0 - 50°C (Full Power) D-Rating of 2.1W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4824M	38 - 63V DC	24V @ 5A	120W	717792.64	0 - 50°C (Full Power) D-Rating of 3.96W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4824R	38 - 63V DC	24V @ 7A	168W	434805.29	0 - 50°C (Full Power) D-Rating of 5.88W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4848M	38 - 63V DC	48V @ 2A	96W	717792.64	0 - 50°C (Full Power) D-Rating of 3.16W per Degree Celcius above 50°C to a maximum of 60°C.
PBIH-4848R	38 - 63V DC	48V @ 3.5A	168W	434805.29	0 - 50°C (Full Power) D-Rating of 5.88W per Degree Celcius above 50°C to a maximum of 60°C.