

AUSTRALIAN RAIL TRACK CORPORATION LTD

Ref No: 08-08-11-035

New Equipment & Systems Approval -Hollow Steel Sleeper for Wayside Equipment Installation

1. Determination of Need

ARTC, in conjunction with the rolling stock operators, is undertaking the installation of rolling stock wayside monitoring equipment at a number of sites in NSW, Vic and SA.

Installation of this equipment requires the running of cables, power and data, to and from the track side monitoring equipment sensors to the data collection and processing equipment located in specially equipped huts at each site.

A mechanism is required to allow the cables to pass from equipment sensors on one side of a track or tracks, to the equipment hut on the other side of the track.

For the monitoring equipment to have maximum effectiveness downtime from damage by ballast or other debris thrown about by passing trains needs to be minimised; to this end, the mechanism by which the cables pass under the track is required to enclose the cables, and to be both robust and long lasting.

2. Significant Change or Not

This change in equipment is assessed as MINOR

3. Review Panel

- John Cowie Manager, ISP, Standards and Systems
- Tim Calver Standards and Technical Services Engineer
- Ian Domleo Senior Track and Civil Consultant

4. Equipment Suitability

Equipment chosen for the task is a steel hollow sleeper as per VAE Railways Systems drawing VAM 13768 rev B (attached).

The sleeper is derived from the in-bearers which are part of the assembly of a 60kg Standard Gauge Tangential Turnout currently being trailed in NSW.

Sleeper cross section, material thickness and grade are the same as for the in-bearer of the Turnout. The hollow sleeper varies in that it is *not* notched at one end as is the in-bearer, removing an area of stress concentration, and there are two lengths of sleeper being used.

- 1. 4.50m to which acoustic monitoring equipment will be mounted; and
- 2. 4.00m, to act only as a cable conduit.



AUSTRALIAN RAIL TRACK CORPORATION LTD

VAE initially undertook a Finite Element Analysis of the turnout in-bearer with attachments as follows.

- 1. VAE Railways Systems drawing number VAM 13768 rev B;
- 2. VAE Railways Systems drawing number VAM 13575 rev D;
- 3. VAE Railways Systems Report *"Finite Element Analysis In-Bearer Systems Version J"*;
- 4. VAE Approval Application Point Layout Operation and Components Inbearer Steel Sleepers for Spherolock; and
- 5. VIPAC Engineers and Scientists LTD drawing number 5656-0114

Further to this analysis Worley Parsons also undertook a Finite Element Analysis (attached) on the in-bearer sleeper to accurately represent the loading conditions experienced. Results varied from the initial analysis completed by VAE and on further inspection of the VAE report it was concluded that the load assumptions were inadequate for the typical condition experienced by the in-bearer sleeper.

1. Worley Parsons 2006, "*ARTC Hollow Sleeper – Final Report*", Document No. 500/09962, Advanced Analysis Division, Victoria.

The suitability of the sleeper was determined to be adequate for its application.

5. Approval

Worley Parsons performed an FEA analysis reviewing the initial VAE analysis, assessment of an improved design, assessment of as-installed arrangement and assessment of unbraced sleeper arrangement for both the 2.6m and 4.5m long sleepers to be installed.

Results obtained for the long sleeper show that the 35t axle load induces a minimum factor of safety of 1.1 in fatigue. As the minimum factor of safety is above 1.0 and with added conservatism within the analysis, the 4.5m long sleeper is proven to be of adequate design.

The short sleeper shows a minimum factor of safety of less than 1.0 in the as-designed configuration. A re-design was performed and analysed in an effort to increase the factor of safety. The re-designed short sleeper has a minimum factor of safety of around 1.2 in the region of a non load bearing weld with an allowable 35MPa (BS 7608:1993). The remaining factors of safety values calculated for the design are all now greater than 1.2 and as such, the design is deemed to be adequate for the proposed load. The final analysis performed gives an indication of the suitability of the design to be used without welding in the struts. The results show that the unbraced design is adequate, with a minimum factor of safety of 1.33, provided the strut has never been installed or has been removed entirely.



AUSTRALIAN RAIL TRACK CORPORATION LTD

The approval for installation of the in-bearer sleepers is warranted at 35t axle load and is applicable ARTC network wide.

6. Conditions of Approval

- All future installations of in-bearer sleepers should be constructed as to *Not* include the cross-braced struts as designed by VAE.
- Only to be installed in track in good complying condition e.g good drainage, ballast depth, compaction, ballast shoulder, well compacted.
- No modification to sleeper <u>whatsoever</u> without written approval from ARTC Standards & Systems department e.g drilling, welding, notching, cutting etc

7. Sign off

Review Panel:

John Cowie	per signed original	Date	07/08/2006
Tim Calver	per signed original	Date	07/08/2006
Ian Domleo	per signed original	Date	07/08/2006

End of document.





12,000	ZX308X738 KOBBER					•			020	00001		
PLATE						6	VAE 8	35554	798	31350000)4	
PIN INBEARER						6	VAM	11482	L71	00009		
ED BY	VAE				•							
		D	PARTS LIST AMEN)ED / DRC	G AMENDED)				11/10/05	СМВ	DPB
		С	BALLAST MAT ADD	ED TO PA	ARTS LIST					05/08/05	СМВ	DPB
		В	ITEMS 9 & 11 MODI	FIED						09/03/05	TQN	GSB
		Α	PRELIMINARY FOR	REVIEW						19/02/05	TQN	GSB
		Rev.			Descriptio	on				Date	Dm.	Ckd.
rawn TQN	Date 16/02/05	Part No. J20	600001	VAE	RAIL	.WAY	SYS	STEMS	PT	Y LTD	Macka A.B.N. 7	ay, Australia 1 011 073 108
hecked GSB	Scale 1:10	Predeces	isor		INBE	AREF	SWI	TCH TIE	E A	SSEMBL	Y	
oproved GSB	Weight (kg)	Specifica A.S	tion 5. 1085.1		FUR	ыка	143	5 GAUG	E IC	JRINOUT	3	
must not be copied or passed on to third persons or made ment. Furthermore, manufacturing of the represented objects g is liable to civil proceeding and criminal prosecution.			Code	Size A1	Sheet No 1 O	». f 1	Dwg. No.	Л	13575		D.	

	BIL	L OF MATERIAL					
ITEM	DESCRIPTION		QTY	DRAWING	F	PART No).
1	STEEL BEARER		2	VAM 13576	E93	00180	
2	IBAV PLATE RIGHT HAND		3	VAM 13577	E25	00104	
3	IBAV PLATE LEFT HAND		3	VAM 13577	E25	00105	
4	PLATE WITH FORGED HORN RIGHT HANE)	1	VAM 13578	E25	00106	
5	PLATE WITH FORGED HORN LEFT HAND		1	VAM 13578	E25	00107	
6	5mm THICK HDPE PAD 591mm LONG		8	VAM 13579	E94	08000	
7	5mm THICK HDPE PAD 410mm LONG		4	VAM 13579	E94	08000	
8	SWITCH MACHINE BASEPLATE		1	WBS33304137	7 3330413701		
9	ANGLE BRACKET SEPERATOR		1	WBS33304138	333	0413801	1
10	"3H" ECCENTRIC INSULATING BUSH FOR	20mm THICK PLAT	16	VAM 13443	E9500031 E9500030		
11	FLANGED INSULATING BUSH FOR 10mm	THICK PLATE	8	VAM 13444			
12	M20 WASHER SPECIAL - ZINC PLATED		24	VAM 13700	L81(L8100019	
13	M20 WASHER STANDARD - ZINC PLATE)	27 27		L1720201		
14	M20 SPRING WASHER - ZINC PLATED				L182	20201	
15	M20 HEX NUT - ZINC PLATED		27		L122	20201	
16	M20 HEX HEAD BOLT 65mm LONG - Z	INC PLATED	8 3		L22	20065	
17	M20 HEX HEAD BOLT 75mm LONG - Z	INC PLATED			L22	2220075	
18	M20 HEX HEAD BOLT 90mm LONG - Z	INC PLATED	16		L22	20090	
19	RAIL CLIP ''K'' TYPE		6	VAM 13445	E93	9300181	
20	M24x60 D-BOLT		6	VAE 87699	L53	24001	
21	M24 NYLOC NUT		6		L132	24204	
22	M24 BELVILLE WASHER		6		450	082934	
23	M27×100 HEX HEAD BOLT COMMERCIAL	BL	2		L32	27080	
24	M27 STRUCTURAL NUT		2		L33	27001	
25	M27 SPRING WASHER		2		L38	27001	
26	BALLAST MAT 12x308x750 RUBBER		4		J28	00054	
27	IBAV SPRING PLATE		6	VAE 85554	798	1350000)4
28	IBAV SPRING PIN INBEARER		6	VAM 11482	L710	00009	
*	ITEMS SUPPLIED BY VAE						
	DP	ARTS LIST AMENDED / DRG AMEND	ED			11/10/05	СМВ
	С В	ALLAST MAT ADDED TO PARTS LIS	т			05/08/05	СМВ





ELEVATION



<u>PLAN VIEW</u>

Typical only

		BILL OF MATERIAL			
	ITEM	DESCRIPTION	QTY	DRAWING	PART No.
A	1	STEEL BEARER 4.5 METRES	٠	VAM 13766	G8000003
	2	STEEL BEARER 2.6 METRES	٠	VAM 13767	G8000004
	3	BASEPLATE INB-PLT1	2	VAM 13769	
	4	5mm THICK HDPE PAD 595mm LONG INB-1	2	VAM 13770	
	5	"3H" ECCENTRIC INSULATING BUSH FOR 20mm THICK PLAT	8	VAM 13443	E9500031
	6	M20 WASHER SPECIAL - ZINC PLATED	8	VAM 13700	L8100019
	7	M20 WASHER STANDARD - ZINC PLATED	8		L1720201
	8	M20 SPRING WASHER - ZINC PLATED	8		L1820201
	9	M20 HEX NUT - ZINC PLATED	8		L1220201
	10	M20 HEX HEAD BOLT 90mm LONG - ZINC PLATED	8		L2220090
	11	BALLAST MAT 12x308x750 RUBBER	2		J2800054
	12	COVER PLATE	1	VAM 13771	J2600004
	13	M20 HEX HEAD BOLT 65mm LONG ZINC PLT	4		L2220065
	14	M20 SPRING WASHER ZINC PLT	4		L1820201
••	15	PANDROL CLIP e2003	4		E9100004

 1 OFF 4.5m STEEL SLEEPER FOR P/No. J2600002 OR 1 OFF 2.6m STEEL SLEEPER FOR P/No. J2600003
 ITEM PACKED

NOTES P/No. 4.5M STEEL SLEEPER ASSEMBLY J2600002 2.6M STEEL SLEEPER ASSEMBLY J2600003

	Dnawn DMJ	Date 07/03/06	Pert No. SEE NOTES	VAE	RAILW	VAY	SYSTEMS	ΡΤΥ	LTD	Mackay, Australia A.B.N. 71 011 073 108	
	Checked	Scale	Pradecessor								
	СМВ	1:10	VAM 13575		INBE/	ARER	TROUGH	ASSE	MBLY		
	Approved	Weight (kg)	Specification	FOR 60KG 1435 GAUGE							
	DPB		AS1085.1			•					
v 0	ad must not be	e conjed or passed or	to third persons or made	Code Si	20 S	heet No.	Dwg. No.			Rev.	
agr i dr an	ement. Furth ing is liable to	ermore, manufacturing o civil proceeding and	of the represented objects criminal prosecution.		A1	1 of	1 VA	<u>M</u> 1:	3768	B	

This drawing is exclusively our intellectual proper accessible to them without our previous writter by the recipient is interdicted. Illegaluse of this

 23/03/06
 DMJ
 DP8

 20/03/06
 DMJ
 CMB

 Date
 Dm.
 Ckd.

B CANTED PLATES ADDED A 5.0M INBEARER CHANGED TO 4.5M IN LENGTH



	∓β Α BC"	F HM	D5FHBLA 69F	8 9G7 F ÐH€ B	GI DD@ 9 F	
	%	&)))&!\$\$\$%	<c``ck gyydyf<="" td=""><td>J 5 9</td><td></td></c``ck>	J 5 9	
	&	&)*)*!\$%%&!&	=gc`Uhcf7cjYf!F][\h		
	I	&)*)*!\$%%&!%	-spc`Uhcf7cjYf!`@YZh		
	(&)*)*!\$%%\$	7 UV]bYh6YUa		IE
)	,)*)*!\$‰+	f⊊c`Uhcf'5ggm		@£
	*	,	A %* 1 &)	GhiGhi < YI i < YUX		A 5
	+	,	A %*	GhiGhiGdf]b[iKUg\Yf		
:	ı	%*	A % 1 ')	GhiGhi < YI < YUX		· t
	-	' &	A %*	GhiGhi D`U]bi K Ug\Yf		
	%\$	%*	A %*	GhiGhi Bhic WBih		' f
		%	&		(

)		7
	O.			9		8
		٦	ур	ica	lonly	9
IB@90G°CH<9FK €9°CD97≑-98°8+A9BG€BG°5F9 -B°A-∞eA9HF9G°°°; 9B9F5@HC@9F5B79G°5F9. @B95F°±\$°% 5B;I@5F°±%	7 C B HF 5 7 H	HBc		J ₽57 ⁻	9B; = B 99F G' · · · G7 = 9B HGHG &%? = B; K = : : : : : : : : : : : : : : : : : :	°@+₿
A 5 H9F - 5 @ 5 G D9F D5 F HG	8F5K B 7<97?98	F"` <ua]`hcb< td=""><td>%+`: 96`\$* !</td><td>^{₩፼} 756-B9H</td><td>IACIBH5009A6@MCB00991</td><td>D9F</td></ua]`hcb<>	%+`: 96`\$* !	^{₩፼} 756- B 9H	IACIBH5009A6@MCB00991	D9F
: -B -€< 5 G D9F D5 F HG ' fX '5 B; @ DFC >97 H€ B	5 DDF C J 98 G97 I F I M7	! @506;≓51+€8 B7@5GG=	! ≑ =98	7с89 ⁻ 898нвс N+:\$,	^{8F5K} ⊕; ^{Bc} *!\$%⁄⁄(G< 99H G₽V9
	8F5K =B;	GH5B85F889	: 'f5 GHL') \$,)	G7 5@9 B#5	G<99HBC *** C:** &	5

+ FUL FUL FUL €GL 9 85H9 8F5K B 7<?8</td> 5DDFCJ 5@ 87 B 5 %+: 96'\$* F"'<Ua]hcb</td> ! ! ! 6 &.: 96'\$* F"'<Ua]hcb</td> I I I 7 *'A 5F'\$* F"'<Ua]hcb</td> I I I

6

%	&		()	*	+	
	H, jojXcW a YbhUbX Ubm]bZcfa Uhjcb cfXYgMfdhj Y	a Uthr/FWcbtUbyX 10Wca a i b1WUhYX 10WcbZXYbWF UbX 10	-	8C BC HG7 5@9		F9J €€ BG! G	99'87 B : C F 89H5 44G
)*)*!\$%/(INY Wedmt] \hdtcdYthmcZJ 405 / '90 [bYYtg/ GWYt cUbYXžWedYXžcfi gYXžcfa Ubi ZJWhi f]0 [`cfhYb) 7 C DMF ≑ <hj '98="" 405="" 448="" 4899="" 498="" 50<="" 7="" ;="" g="" g7="" h44g="" p=""></hj>	ohgng @a, phrX°BYph.YfhXYk,∖cYcfUbmYIh1UWha.UmVYX)gWcg/Xž Xfp[difdcg/gk]h∖cih1h,Y]fk,1phYb.Wcbg/bh* 3D9F @5H9CH85H97C: =5CI9C <ck,b*69@ck< th=""><th></th><th></th><th>€G F</th><th>9 85H9 8F5K E</th><th>7 <?8 5DDFC J 5@ 87 B</th></th></ck,b*69@ck<>			€G F	9 85H9 8F5K E	7 8 5DDFC J 5@ 87 B</th
⁵ 1 G98 °C B					5	%+:96'\$* F <uaji & 96'\$* F"<uaji< th=""><th>cb i j 5</th></uaji<></uaji 	cb i j 5
					7	* A 5F \$* F" < Ua]t	cb
			1				
			4	• • •	•	o	
6							6
				· ·			
			\$	÷ •		$\left \bigcup \right $	
			~ -			 ∙ • 	
			\$	×		. .	
			- 00			ŀ · Ⅰ	
			$\ddot{\circ}$				
1							1
			Π	• •	•	۰	
			V				
· ,)				\square	(\$-\$		
8							8
		&)					
\square					&%)\$		
Y		0::.					
A							
		I					
					2())		9
9					()) 4		
				IB@90GCCHk9FK €910D97 ≑ -98 8 ≠ A9BG€BG5F9 -BA_@@A9HF9G``; 9B9F5@HC@9F5B79G5F9.	/ U B H D / HBC	J ₱25 7 9B;	+ + + + + + + + + + + + + + + + + + +
				@#5 y5 F ± \$"& 5B; I @5 F ± %			5"7 "B":\$\$) '()' '*&+
	I \/r	ncal only		5 G D9F D5 FHG	8F5KB F" < Ua jhcb %+': 96" 7 < 97 ? 98 I I	⁵ * ^μ ^μ ^ω 756- R 9HΔ C	IBH5009A 6aMCB 0a9009F
:	I Y N				5 DDF C J 98 ! !		
		-		:⊎€x 56D9FD5FH6	G97 I F ≢M7 @5 GG≑ 7 5 H€ B	7С89 ⁻ -89ВНВс 8F5	(書): Bc く 書): Bc (品): G=499 (品): G=499
				' fX :5B; @9'DFC >97 H€ B →	IB7@5GG≑=98	N+: \$,)^)^!\$%%(<mark></mark> '
%	&	•	(8F5K -B; "GH5B85F8"""89: "f5I GH2")\$,	,) G7 5 @9 ⁻ B#5	G< 99HBC % C: %